



# STACK DECK - Upper Work Area Access Towers

Safe Anti Slip Deck Access to Work Areas for Reach to 20' - folds down flat

All Aluminum Stacking Stages with 4 way handrail & 2 entry gates. Foldable for transport.

Weather resistant 6061 aluminum construction. All assemblies with fasteners in place for quick set up. 6" double locking castors, 880 lb rated. Vertical frames are thick wall tube, 6061 temper.

Heavy Duty 6061 Aluminum frame. Type 1 (250 lbs rated) extension ladder. Type 1a (300 lbs) / 1aa (375 lbs) extra. Photo set up & safety instructions. OSHA & CSA safety compliant.

### 30 x 36" anti slip deck: double locking wheels

Service upper areas safely with anti slip deck approach

Access rooftop & ceiling areas

Change ceiling mounted fixtures safely

**2 Stages**

96" deck height

Figure 4

SD30368A

**2 Stage with top adjusting stage**

78" to 96" deck height

Figure 1, 3

SD30368A

call for pricing

**3 Stages with top adjusting stage**

126" to 144" deck height

Figure 2

SD303612A

**2 stage 20 x 24" model**

78" to 96" deck height

Figure 5

*under further development*



### Systems: Join 2 Stack Decks with Bridge Plank

call for pricing

Bridge over obstacles to heights of 12' with top & midrails (not shown).

Accessories include tool trays & deck padding to protect painted surfaces.

2 : 78"-96" height Stack Decks with 10' length x 20" wide bridge plank

SD810Sys20

2 : 78"-96" height Stack Decks with 10' length x 30" wide bridge plank

SD810Sys30

2 : 126"-144" height Stack Decks with 10' length x 20" wide bridge plank

SD1210Sys20

2 : 126"-144" height Stack Decks with 10' length x 30" wide bridge plank

SD1210Sys30



### Custom Applications - Send us your access & fit challenges

Transit Maintenance Facility Rooftop: 10 - 2 stage 30" x 36" x 96" height models to gain access to green energy exhaust reclamation stacks.

We added custom footings, upgraded to 375# rated ladders and widened handrails.

