

# Confined Area Rooftop Containment Systems

Apr 3, 2023


**Engineered Systems: Protect workers from harmful falls - 96" x 102" wide containment**

Weather resistant 6061 aluminum construction. All assemblies with fasteners in place for quick set up.  
Powered lift with your drill driver. 8" locking castors. Perforated dimple anti slip channel step & deck access.  
Heavy Duty 6061 Aluminum frame. Type 1 (250 lbs rated) extension ladder. Type 1a (300 lbs) / 1aa (375 lbs) extra.  
Photo set up & safety instructions. OSHA & CSA safety compliant. Welded in Summerland, BC  
Lower kick rail upon request.

**Step Access** *YouTube video link on our website* 30" x 10" landing step 96" x 102" surround rail  
**Engineered & stamped compliant with Can/CSA 354.1-04 Portable Elevating Work Platform**

Forward anti tip wheeled frame, side support hydraulic levellers with 300 lbs counter weights

**Class C** 9' 6" to 12' 6" height range *PRCS126*  
**Class A & 5th Wheel** 9' 6" to 14' height range *PRCS14* Call for pricing  
**Tilt Back Option** for 14' door entry *TBO*



Tilt Back




lower toe boards upon request



Adjustable lower rail option to adjust for 5th wheel roof slopes

**Deck Access** *YouTube video link on our website* 10' x 30" deck alongside 120" x 102" surround rail  
Class C, Transit Bus Sidewall access to 12' 8" max *PRCSD128* Call for pricing  
Class C & A, 5th Wheel Sidewall access to 13' 8" max *PRCSD14*



Lower toe boards upon request

